

## CK WORLDWIDE TIG TORCH POWER GAS COOLED CONNECTORS

FITS POWER CABLES WITH A MALE THREAD 7/8"-14 RIGHT HAND

If your machine has the gas flow through the female power connection then you would use the GAS-THRU Connector.

FITS TORCHES CK26, TL26, CK210, TL210, CKM210

### DINSE CONNECTORS

DINSE 25  
(3/8" 9.5mm)




DINSE 35  
(1/2" 12.8mm)



DINSE 25M  
(3/8" 9.5mm)



DINSE 35M  
(1/2" 12.8mm)



STANDARD

#### STANDARD

DINSE SIZE	CK26 CABLES	CK210 CABLES
3/8" (9mm)	<b>SL8-25</b>	<b>SL5-25</b>
1/2" (12.8mm)	<b>SL8-35</b>	<b>SL5-35</b>



GAS-THRU

#### GAS-THRU

DINSE SIZE	CK26 CABLES	CK210 CABLES
3/8" (9mm)	<b>SL8-25M</b>	<b>SL5-25M</b>
1/2" (12.8mm)	<b>SL8-35M</b>	<b>SL5-35M</b>



TWECO OR  
CAM-LOCK

#### TWECO / CAM-LOCK

DINSE STYLE	CK26 CABLES	CK210 CABLES
TWECO	<b>SL-8</b>	<b>SL-5</b>
CAM-LOCK	<b>SL8-CL</b>	<b>SL5-CL</b>

### 45V62



Used with:  
CK26, TL26

7/8"-14 RH

5/8"x18 RH

ALSO FITS TL210 AND CKM210